



1" & 2.5"

MAIN VAULT DOOR SERIES



PRIVACY • SECURITY • ASSET



STRENGTH




CUSTOMER SERVICE



WORLD CLASS

SPECIFICATIONS



Ref	Specifications (mm)	1" Main Vault Door	2.5" Main Vault Door
A	Barrier Material Thickness	25	70
B	Overall Door Thickness	162	182
C	Recommended Wall Thickness	200	200
(D)	Wall Opening Required - Height	2,300	2,300
E	Wall Opening Required - Width	1,400	1,400
(F)	Overall Height of Frame	2,169	2,170
G	Overall Width of Frame	1,190	1,206
(H)	Clear Opening - Height	2,000	2,000
I	Clear Opening - Width	900	900
J	Overall Width When Door Open at 180 Degree	2,120	2,148
K	Projection When Door Open at 90 Degree	1,037	1,050
L	Projection When Door Open at 180 Degree	237	256
M	Overall Width of Gate When Open at 180 Degree	2,044	2,044
N	Projection of Gate When Open at 90 Degree	975	975
O	Projection of Gate When Open at 180 Degree	65	71
	Moving Bolts / Bolts Diameter 38 mm	11 Sets	11 Sets
	Fixed Bolts / Bolts Diameter 38 mm	7 Sets	7 Sets
	Weight +/- 10 %	620 kg	660 kg

QUALIFICATIONS



SSI (Structural Steel Integration)

Crafted from reinforced thick steel and seamlessly welded, boasts a strong unified structure that is highly resistant to forced entry and nearly indestructible.



XLarge Bolts

Equipped with 38 mm diameter bolts and rust-resistant coating, these locks strengthen the door panel and protect against prying and cutting, enhancing security.



CS350 Barrier Material

The CS350-infused material boasts fire resistance, anti-drill strength, and extra thickness for superior protection against heat, impact, and fire.



Multi Protection Door

The door features 162 mm or 182 mm thickness, reinforced with 25 mm or 70 mm alloy steel and reinforced hinges for enhanced security.



S&G Combination Lock

The UL-certified S&G combination locks feature a 4-digit code with over 100 million possible combinations and include a combination ring to deter code theft.



8 Lever Key Lock

This lock has an 8-lever, double-bit system and comes with a durable, hard-to-copy metal key, increasing security against counterfeiting.



Automatic Relock System

The safe has an automatic relock system with safety glass and a solid code mechanism to prevent tampering, ensuring reliable security.



Drill Protection Alloy Steel

With a puncture-resistant steel plate made from a custom alloy, it protects the key code mechanism, keys, and all points.



High Quality Paint

The door has been polished and treated for rust prevention before being painted in an automotive oven to ensure a long-lasting and shiny finish.

